

LOCKING OPTIONS



Abloy-Classic is a standard lock. Master key Included.



PUNTA cylinder lock



Locking mechanism for padlocks



Card lock



Number lock with master key



Electronic number lock



Abloy Exec 1€ deposit lock (not for doors under 197 mm high) or collecting coin lock (not for doors under 400 mm high). Coin lock doors equipped with pullback spring.



DOOR MODELS

Steel doors



Standard steel door

Steel door: Door thickness 19 mm. Steel thickness 0,75 mm.
Sandwich door: Door thickness 19 mm. Steel thickness 0,75 mm.
Reinforced steel door: Door thickness 20 mm. Steel thickness 2,0 mm.
Reinforced sandwich door: Door thickness 20 mm. Steel thickness 2,0 mm. For special order only.



Perforated steel door



Steel letter box door (for LK4, LK8, LK10 and LK12 lockers)

Colours for steel doors, see PUNTA colour chart. Cylinder locks and locking mechanism for padlocks fits all steel doors. Coin deposit lock fits sandwich doors.

Wood doors



18 mm laminated door with 8 mm wooden batten

Body of laminated and veneer doors is made of chipboard. MDF bodies without batten can be laminated, which is a lower price option.



18 mm veneer door with 8 mm wooden batten

Colours for laminated doors, see e.g. Formica Collection. Veneer doors, also tinted, available in general wood species. All locking options available for wood doors.



19 mm painted MDF door standard colour white

Louvred doors



Lacquered pine, birch, beech or oak louvred door (Louvred doors more than 400 mm high)



Painted louvred door

Window doors/ aluminium frame doors



Acrylic window door, colour light smoke grey (Aluminium frame doors more than 400 mm high)



High pressure laminate aluminium frame door (thickness 6 or 10 mm)

Colours for high pressure laminate doors, see e.g. Formica Collection.

Cylinder locks, coin deposit locks or locking mechanism for padlocks are available.