

PUNTA Charging Locker

Standard heights	880mm, 1,700mm (without base); other heights available on order
Number of stacked lockers	12 (LK12, H: 122mm), 6 (LK12, H: 122mm) 10 (LK10, H: 150mm), 5 (LK10, H: 150mm) 8 (LK8, H: 192mm), 4 (LK8, H: 192mm) 4 (LK4, H: 397mm)
Module width	300mm or 400mm (aperture width: 224mm, 324mm)
Depth	532mm + 20mm, on order 402mm + 20mm Ventilation strips at the back of the locker add 20mm to locker depth
Base	Base height: 200mm Maximum width: 1,200mm (max. 3 or 4 modules in parallel) Equipped with adjustable feet (adjustment 50mm) Charging lockers can also be equipped with wheels
Frame material	Cold rolled 0.75mm steel sheet.
Door material	A suitable material can be selected from our wide range
Ventilation	All lockers come with holes in the back wall. In case of wall mounting, ordering the lockers with back wall elevation bars is recommended
Colour	In addition to the standard grey, all options in our colour chart are available.
Power supply	Number of sockets: 1 per locker (LK4 available with 2 sockets) Optional USB unit in place of regular socket (2 USB sockets, max. 2.1A)
Maximum power	2500W (10A, 250V)
Power cable length	2.5m (can be changed)
Power cable connector location	locker top
Power cable connector to charging locker	IEC C13 angled
Mounting	With wall mounting kit
Lock	A lock suitable for the purpose can be selected from our wide range
Accessories	LAN socket in each locker
Safety	Only compatible devices may be connected to the sockets
CE marking	The product complies with CE marking requirements

